



PRODUCT DATA SHEET

Lubritex Frictio 4T (Four Stroke) Synthetic Blend Engine Oil SAE 10W-30, 10W-40, 20W-50 API SL, JASO MA2

Product Description

Lubritex Frictio Synthetic Blend Engine Oils 4T (Four-Stroke) are parasynthetic, high-performance, multi-grade lubricants for use in high-RPM, 4-stroke motorcycle engines with integral gear boxes and wet clutches as well as for use in any application requiring a four-stroke engine oil meeting the requirements of JASO MA2, JASO MA or API SN. Blended with synthetic basestocks and premium performance additives, **Lubritex Frictio Synthetic Blend Engine Oils 4T (Four-Stroke)** provide excellent protection during rapid RPM increase. Specialty friction modifiers provide for smooth clutch and gear shift operation while specialty anti-oxidants and sophisticated dispersant technology provide enhanced cleanliness. **Lubritex Frictio Synthetic Blend Engine Oils 4T (Four-Stroke)** are highly shear stable therefore eliminating viscosity breakdown. These products are parasynthetic multi-grade engine oils suitable for use in all seasons.

Typical Properties*

| SAE J300 Viscosity Grade | 10W-30 | 10W-40 | 20W-50 |
|--|----------------------------|---------------|---------------|
| Appearance, Visual | Amber, Transparent, Liquid | | |
| Viscosity @ 40°C, cSt, ASTM D445 | 69.55 | 97.25 | 160.55 |
| Viscosity @ 100°C, cSt, ASTM D445 | 11.0 | 14.5 | 18.5 |
| Viscosity Index, ASTM D2270 | 150 | 155 | 130 |
| CCS Apparent Viscosity, cP, ASTM D5293 | 4,800@-25°C | 5,200@-25°C | 7,000@-15°C |
| MRV Apparent Viscosity, cP, ASTM D4684 | 16,000@-30°C | 23,000@-30°C | 18,000@-20°C |
| Flash Point, °C, ASTM D92 | 215 | 215 | 220 |
| Pour Point, °C, ASTM D97 | -42 | -40 | -30 |

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Suitable for Use:

API SL
JASO MA2
JASO MA

Product Codes:

SAE 10W-30 - SXF190
SAE 10W-40 - SXF191
SAE 20W-50 - SXF192

